



US007302364B2

(12) **United States Patent**
Fussell et al.

(10) **Patent No.:** **US 7,302,364 B2**
(45) **Date of Patent:** **Nov. 27, 2007**

(54) **METHODS AND SYSTEMS FOR ADVANCED
SPACEPORT INFORMATION
MANAGEMENT**

(75) Inventors: **Ronald M. Fussell**, Cocoa, FL (US);
Donald W. Ely, Titusville, FL (US);
Gary M. Meier, Rockledge, FL (US);
Paul C. Halpin, Orlando, FL (US);
Phillip T. Meade, Merritt Island, FL
(US); **Craig A. Jacobson**, Cocoa, FL
(US); **Charlie Blackwell-Thompson**,
Merritt Island, FL (US)

(73) Assignees: **The Boeing Company**, Chicago, IL
(US); **The United States of America as
Represented by the Administrator of
the National Aeronautics and Space
Administration**, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/083,420**

(22) Filed: **Mar. 17, 2005**

(65) **Prior Publication Data**

US 2006/0038084 A1 Feb. 23, 2006

Related U.S. Application Data

(60) Provisional application No. 60/593,014, filed on Jul.
30, 2004.

(51) **Int. Cl.**
B04G 1/00 (2006.01)

(52) **U.S. Cl.** **702/188**

(58) **Field of Classification Search** 702/188,
702/33, 35, 36; 701/3, 2, 29, 30, 31

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,466,063 A	8/1984	Segarra et al.
5,152,482 A	10/1992	Perkins et al.
5,314,146 A	5/1994	Chicoine et al.
5,317,689 A	5/1994	Nack et al.
5,355,238 A	10/1994	Kight et al.
5,474,262 A	12/1995	Fiore
5,518,209 A	5/1996	Chicoine et al.
5,623,357 A	4/1997	Kight et al.
5,624,088 A	4/1997	Fiore
5,755,406 A	5/1998	Aston et al.
5,801,938 A	9/1998	Kalantery

(Continued)

OTHER PUBLICATIONS

<http://www.m-w.com/dictionary/emulate>, p. 1.*


Primary Examiner—Tung S. Lau

(74) *Attorney, Agent, or Firm*—Lee & Hayes, PLLC

(57) **ABSTRACT**

Advanced spaceport information management methods and systems are disclosed. In one embodiment, a method includes coupling a test system to the payload and transmitting one or more test signals that emulate an anticipated condition from the test system to the payload. One or more responsive signals are received from the payload into the test system and are analyzed to determine whether one or more of the responsive signals comprises an anomalous signal. At least one of the steps of transmitting, receiving, analyzing and determining includes transmitting at least one of the test signals and the responsive signals via a communications link from a payload processing facility to a remotely located facility. In one particular embodiment, the communications link is an Internet link from a payload processing facility to a remotely located facility (e.g. a launch facility, university, etc.).

12 Claims, 6 Drawing Sheets




US 7,302,364 B2


Page 2


U.S. PATENT DOCUMENTS

5,812,528	A	9/1998	VanDervort	6,507,809	B1	1/2003	Yoshino et al.
5,961,076	A	10/1999	Eller et al.	6,684,192	B2	1/2004	Honarvar et al.
6,108,309	A	8/2000	Cohoe et al.	7,020,797	B2 *	3/2006	Patil 714/4
6,242,873	B1	6/2001	Drozdz et al.	2002/0123832	A1 *	9/2002	Gotvall et al. 701/33
6,405,173	B1	6/2002	Honarvar et al.				

* cited by examiner

*FIG. 1*

**FIG. 2**

*FIG.3*




FIG. 4A




FIG. 4B




FIG. 5

1

METHODS AND SYSTEMS FOR ADVANCED SPACEPORT INFORMATION MANAGEMENT

PRIORITY CLAIM

This application claims priority from the U.S. Provisional Patent Application No. 60/593,014 entitled "METHODS AND SYSTEMS FOR ADVANCED SPACEPORT INFORMATION MANAGEMENT" filed on Jul. 30, 2004, the contents of which are incorporated herein by this reference.

GOVERNMENT LICENSE RIGHTS

The invention described herein was made in the performance of work under Contract Nos. NAS10-02007 and NAS10-11400 administered by the National Aeronautics and Space Administration, and is subject to the provisions of Section 305 of the National Aeronautics and Space Act of 1958 (72 Stat. 435; 42 U.S.C. 2457). The United States Government has certain rights to this invention.

FIELD OF THE INVENTION

The present disclosure relates to information management systems, and more specifically, to methods and systems for advanced spaceport information management, including, for example, test and verification systems for spaceflight payload testing.

BACKGROUND OF THE INVENTION

It is very important that the operational characteristics of payloads that are to be transported into space aboard launch vehicles be tested and verified prior to launch. For example, the requirement to perform testing of payloads that are intended to be launched aboard the Space Shuttle is founded upon the Space Shuttle Program Directives NSTS 07700 of the National Aeronautics and Space Administration (NASA). The need to test payloads prior to launch is primarily based upon the need to mitigate risk to launch and on-orbit operations.

The testing of high-value, often one-of-a-kind spaceflight hardware has historically remained a source of high cost for the payload developer. In terms of travel and transportation of the developed payload and support personnel to the launch site, testing costs have historically been driven by external factors, including scheduling of tasks, resource availability, and geographic concerns. Additionally, the far-reaching and complex nature of the problems encountered during payload processing at the launch site present substantial challenges to efforts to control costs while at the same time maintaining a high degree of technical quality. Therefore, improved payload testing techniques that at least partially mitigate the cost and complexity of the prior art test and verification methods would be valuable and useful. These issues are increasingly evident in the transition from dedicated hardware processing and launch sites to a Spaceport environment, where payload processing is less a launch site undertaking.

SUMMARY OF THE INVENTION

The present invention is directed to methods and systems for advanced spaceport information management and transitional capabilities thereto. Methods and systems in accordance with the present invention may advantageously re-

2

cate test operations that are traditionally performed at the launch site to the payload developer location, thereby reducing the processing time required at the launch site, reducing the dependency upon launch site infrastructure, and reducing costs and promoting a distributed teaming approach to payload test and verification. This allows the evolution from current operational scenarios to the Spaceport operations approach to space access.

In one embodiment, a method for testing a payload includes coupling a test system to the payload and transmitting one or more test signals that emulate an anticipated condition from the test system to the payload. One or more responsive signals are received from the payload into the test system and are analyzed to determine whether one or more of the responsive signals comprises an anomalous signal. At least one of the steps of transmitting, receiving, analyzing and determining includes transmitting at least one of the test signals and the responsive signals via a communications link from a payload processing facility to a remotely located facility. In one particular embodiment, the communications link is an Internet link from a payload processing facility to a remotely located facility (e.g. a launch facility, university, etc.) or accommodated by models found within the remotely configurable test interface.

BRIEF DESCRIPTION OF THE DRAWINGS

The preferred and alternative embodiments of the present invention are described in detail below with reference to the following drawings.

FIG. 1 is a schematic view of a test and verification system in accordance with an embodiment of the invention;

FIG. 2 is a method of test and verification of a payload under test in accordance with an embodiment of the invention;

FIG. 3 is a schematic view of a set of software components of a hardware (i.e. remotely configurable test interface) system in accordance with another embodiment of the invention;

FIG. 4A is a schematic view of an avionics software tasking model in accordance with another embodiment of the invention;

FIG. 4B is a schematic view of a test and verification system in accordance with yet another embodiment of the invention; and

FIG. 5 is a schematic view of an integrated spaceport automated data management architecture in accordance with another alternate embodiment of the invention.

DETAILED DESCRIPTION

The present invention relates to methods and systems for advanced spaceport information management and transitional capabilities thereto. Many specific details of certain embodiments of the invention are set forth in the following description and in FIGS. 1-5 to provide a thorough understanding of such embodiments. One skilled in the art will understand, however, that the present invention may have additional embodiments, or that the present invention may be practiced without several of the details described in the following description.

In brief, embodiments of the present invention take advantage of a distributed teaming concept for the processing of payload test requirements. Emerging networking technology advantageously allows for the capability through assured command and telemetry integrity. By exploiting such a distributed teaming concept, the testing of payload

components and subsystems may be accomplished at the location of the payload developer prior to transport of the payload to the launch site. For payloads with components developed in more than one location, integration at a common site will still be required. Furthermore, relocating test operations that are traditionally performed at the launch site to the payload developer location typically results in a reduction in processing time required at the launch site (e.g. Kennedy Space Center), and may also reduced dependency upon launch site infrastructure. In turn, the costs associated with testing traditionally performed at a centralized location, such as the launch site, may be reduced.

FIG. 1 is a schematic view of a portable test and verification system (PTVS) **100** in accordance with an embodiment of the present invention. In this embodiment, the system **100** includes a front end **110** that is adapted to communicate with a payload **112**, and a back end **120** that is adapted to communicate with the front end **110** and with a payload test team **130**. The payload test team **130** may be remotely located, and may communicate with the back end **120** via a communication link **132** (e.g. a global computer communication network, a wireless link, etc.). The back end **120** may be further adapted to communicate with a payload data repository **140**.

In an alternate embodiment, the back end **120** may be co-located with the payload test team **130** at a remote location, and may communicate with the front end **110** co-located with the payload **112** at a payload test facility via a communication link **132**. In yet another embodiment, the back end **120** and the front end **110** may be co-located with the payload test team **130** at a remote location, and may communicate with the payload **112** at a payload test facility via a communication link **132**. In further embodiments, the payload data repository **140** may be co-located with any of the payload test team **130**, the back end **120**, the front end **110**, and the payload **112**, or may be located at an entirely different remote facility and may communicate via a second communication link.

The system **100** may be a portable payload checkout unit with a domain architecture that allows configuration and deployment for use on multiple payloads at diverse payload developer sites, and may easily accept upgrades and expansions. In this embodiment, the system **100** is characterized as a basic functioning system to support a generic test environment that is reconfigured to variations tailored to the needs of the payload interfaces and scope of the risk to be mitigated. The system **100** may be shipped via commercial carriers and may retain realistic launch vehicle interfaces and capacity to store data, as well as control and monitor ground support equipment. As described more fully below, the system **100** may provide for a distributed team approach utilizing computer communication network (e.g. Internet) applications and protocols.

In one embodiment, the system **100** may be highly automated with self-checking and monitoring capabilities to ensure minimal user interaction requirements. These checks, for example, may include provisions for disk drive and data storage media monitoring to notify the user prior to the manifestation of an anomaly. Such notifications may be based upon current system status coupled with resident trend data to predict potential problems. Corrective action to correct potential problems may involve activation of pre-programmed operations, or manual intervention by a user or system administrator, to rectify the error condition. Additional automation features may include, for example, the tracking of user files to allow purging of these files at pre-determined periods.

Additionally, the networking of test team members from differing locations via secure Internet connectivity may advantageously support a broad exposure to the testing operation, thereby fostering a synergy and ideas in the event of an anomalous condition. Tests again joining may become more effective through the use of the distributed team approach by reducing the need for the travel of team members to the test site.

A system management feature **124** of system **100** may be focused upon the changing requirements of the system. In the embodiment shown in FIG. 1, the system management feature **124** is integrated into the back end **120**. As system requirements change, the hardware and software may be configured per the system requirements followed by a pre-shipment test to ensure operability. The distributed nature of the system **100** may allow real-time services to be administered from the launch site or alternate location as the need arises. These services may include providing remote assistance for troubleshooting efforts required for either the system **100** or the payload **112** under test. Remote support capability and disaster recovery of the system **100** may be facilitated through the employment of appropriate technical strategies implemented prior to shipment to the payload developer location. Additionally, real-time monitoring of payload elements may also be performed remotely on the system **100** through coordination with the payload developer. Monitor and command capabilities of the system **100** from the launch site may also be incorporated into the system designed to facilitate fault isolation and remediation of test system related anomalies. A common engineering database (e.g. the data repository **140**) may be created and stored for distributed access to support commanding and test parameter storage. In addition, test data may be available in a real-time format to those team members with the appropriate permissions.

The system **100** may advantageously provide improved capability for testing at a payload development facility rather than at a final launch facility. As the payload **112** progresses from the early stages of development through integrated testing, the interface, command, and measurement definitions performed by the system **100** may evolve. For example, initially the definition may be applied to the interface directly at the payload **112**, whereas in integrated testing the definition could include spacecraft or payload routing and structure that is stripped off or added by systems communicating with the payload **112**. In a representative embodiment, the design of the system **100** is centered on a small, portable test solution that is readily accommodated by general office type of support, such as standard power and indications. Management of interfaces may be accomplished through the use of remote commanding or on-board simulation and modeling accommodations.

In the embodiment shown in FIG. 1, user notifications for the completion of major test activities where the identification of parameters that are beyond established specifications may be accomplished by the back end **120**. During periods of component testing by the payload developer, the Internet connectivity may not be required and therefore may be accomplished without network connection **122**. In this instance, any conformance report data normally replicated to the data repository **140** via the network connection **122** or may be archived locally for download to the appropriate repository **140** at the next connection opportunity.

The system **100** may take full advantage of portability and maintenance attributes through the minimization of hardware requiring continual maintenance and calibration, while maximizing software asset properties of configure ability

5

and flexibility. Efficient system maintenance and repair may be afforded through the integration of automated fault trees and diagnostics, as well as interleaved and built-in-test equipment for the system **100** and for nominal characterization, troubleshooting, and remediation. Remote operation and troubleshooting capabilities for the system **100** may exist through remote system safety and isolation, troubleshooting, and maintenance commanding. Self-test, system safety, and troubleshooting capabilities are founded upon the concept of a configuration independent architecture, thereby eliminating the need to disconnect from a flight element under test in order to assure system confidence. Development of flight system command sets are facilitated by the on-board test system software and database configuration management capability.

As further shown in FIG. 1, a software wizard **126** may be an integral part of a total test configuration, and may act as a tool for planning and instituting specific test configurations of the system **100**. The software wizard **126** may accommodate the payload developer in identification of test configuration requirements, the posting of testing event milestones, and the generation of schedules and reports (i.e. status of requirement satisfaction, system configuration, problem reporting trend analysis, etc.) needed to coordinate integrated launch site activities prior to need.

The system **100** further includes an onboard scripting and procedural development capability **128**. The interactivity between the scripting and procedural development capability **128** and the test schedule, generated as a result of the initial interview conducted by the software wizard **126**, provides for comprehensive view of planned testing and major payload processing operations. In addition, the scripting and procedural development capability **128** may include the ability to announce anomalous conditions, initiate the documentation of those conditions, render a method of constraining further testing if not technically feasible or unsafe, and support troubleshooting of the malfunction.

Control and monitoring of the system **100** may be performed through a main screen graphics user interface (GUI) display **129**. This display **129** may offer quick assessment of all health and status characteristics of the system **100** by means of, for example, color-coded display graphics (e.g. green for nominal operations, yellow for condition requiring immediate attention, and red for anomalous conditions).

FIG. 2 is a method **200** of test and verification of a payload under test **112** in accordance with an embodiment of the invention. The method **200** begins at a block **202**. Prior to interface of the system **100** (FIG. 1) with spaceflight hardware (e.g. the payload under test **112** or a launch vehicle), a full self-test and system diagnostic may be performed at a block **204** to ensure the operator's confidence in the ability of the system **100** to safely and efficiently perform the desired test operation. Such a self-test may also accomplish the verification of connectivity interface configuration and response to input modeling, and may assure the proper configuration and operation of appropriate security devices (i.e. encryption accommodations, intrusion detection, system monitoring, etc.) of the system **100** to launch site networking assets (e.g. the test team **130**) for distributed teaming operations.

In this embodiment, the method **200** further includes operatively coupling the system **100** to the payload under test **112** at a block **206**. At a block **208**, the test and verification system **100** transmits one or more signals to the payload under test **112** to emulate conditions that the payload under test **112** may be expected to experience during flight operations. The signals transmitted by the system **100**

6

to the payload **112** may include, for example, command signals that activate certain systems or actions to be performed by the payload **112**, and test data signals that the payload **112** may be expected to receive, analyze, and interpret during flight operations. The test and verification system **100** then receives one or more responsive signals from the payload under test **112** at a block **210**, and analyzes the responsive signals from the payload **112** at a block **212**.

At a block **214**, a determination is made regarding whether a responsive signal represents an anomalous condition. If not, then at a block **216**, the method **200** determines whether test and verification of the system **100** is complete. If not, then the method **200** returns to the emulation of flight operations at block **208**. If test and verification is determined to be complete, then the method **200** terminates at a block **218**.

As further shown in FIG. 2, if the method **200** determines that the responsive signal represents an anomalous condition at the block **214**, then at a block **220**, the occurrence of the anomalous condition is identified to the system operator via display accommodations. Upon the discovery of the test parameter that is out of tolerance with the procedural input, at a block **222**, a dialog box may be displayed on the system display that queries if the user would like to generate a nonconformance report.

If the dialog box (block **222**) is answered "yes", then at a block **226**, a nonconformance report is generated and the malfunction is logged flagging any procedural (and operational) constraints, the test module and step where the constraint applies, whether re-test of the affected module is necessary, and finally, transmits nonconformance to the payload data center **140** while maintaining a copy on board. The copy in the payload data center **140** may be accessible by launch site personnel for resolution, if required, and to the payload developer personnel through the back end **120**.

If the answer is "no", then at a box **224**, a second box will inquire as to whether the user wishes to retest the condition, troubleshoot (terminating the test script at that point and manually providing parameters and rejoin the test script at the next major test module), or exit the script thereby terminating the system testing script. If the user wishes to retest the condition, then the method **200** returns to block **208** to allow retesting to be performed. Alternately, if no retesting is desired, the method **200** proceeds to a block **228** to continue or to terminate.

In alternate embodiments, retest capabilities of an anomalous condition may be provided via display and software interaction relating to the malfunctioning feature. Maintenance logs may be resident within the system **100**, as well as within the payload data center **140**, to assure it easy access by authorized system troubleshooters. The efficient troubleshooting and repair of anomalies related to remotely assigned system **100** may be assisted through the employment of a help desk activity that resides at the launch site.

Embodiments of methods in accordance with the present invention advantageously improve the distributed teaming approach to the test and verification of payloads. Specifically, at least one of the transmitting one or more test signals, receiving one or more responsive signals, analyzing one or more responsive signals, and determining whether one or more of the responsive signals comprises an anomalous signal involves transmitting at least one of the test signals and the responsive signals via a communications link from a payload processing facility to a remotely located facility. This advantageously allows personnel from various facilities (e.g. a payload processing facilities, launch site facilities, universities, governmental facilities, etc.) to be

involved in the test and verification procedure via a communication link (e.g. an Internet link) between different cities, different states, and different countries.

A computer program that embodies a method of testing and verifying payload operational capability (e.g. the method **200** shown in FIG. **2**) may be stored on a computer-readable medium that may be uploaded into the memory of the hardware system and may be used to test and verify the performance of the payload.

More specifically, FIG. **3** is a schematic view of a set of software components **400** of a hardware system in accordance with another embodiment of the invention. As shown in FIG. **3**, a CPU **402** of the Payload Model Development computer is coupled to a memory **404** which, in turn, is coupled to a Message Sequence Chart **406**. The Message Sequence Chart **406** transmits data to and receives data from a data bus **408**. Similarly, a Memory Management Unit (MMU) **410**, a digital switching array **412**, a first Multiplexer/Demultiplexer (MDM) module **414**, and a Personal Computer Memory Management Unit (PCMMU) **416** are also coupled to the data bus **408**. A signal and power source **413** is connected via digital switching array **412** to the cable interface **414** to the flight system under test.

An Information Sharing Protocol (ISP) server **418** is coupled to a memory **420** which, in turn, is coupled to a communications program (nicknamed "Snoopy") **422**. The ISP server **418** distributes telemetry and computer data to remote users (not shown). The communications program **422** gathers telemetry information from the PCMMU **416** and makes it available to the user applications through the ISP server **418**.

With continued reference to FIG. **3**, a set of test simulation models **424** (e.g. System/Simulation Infrastructure (S/SI) managed models) is coupled to the SIMEXEC **426**. The SIMEXEC **426** communicates with the data bus **408** via the first MDM module **414**. A second MDM module **428** is coupled between the SIMEXEC **426** and a second data bus **430** which, in turn, is coupled to the PCMMU **416**.

In operation, the test simulation payload models **424** may reside on a model/command development computer and may allow a user to verify and validate the operation of the item under test, and may be used to test the interface between ancillary test equipment and the system under test. Payload data may be placed in the SIMEXEC **426** on, for example, Scramnet Reflective Memory, which may advantageously allow data communication between the mission simulation payload models **424** and the other elements of the system via a shared memory interface. The SIMEXEC **426** provides the seamless management of models and the formulation of digital switch configurations to provide the needed test input to the payload or system under test. This may be in response to scripted input, manually input test parameters, or operational model. Models resident in the System/Simulation Infrastructure (S/SI) model environment **424** are established prior to the attachment of the test system to the payload or system under test to prevent the introduction of spurious, erroneous signals or voltages into the test article. This is accomplished via CPU **402** or network connection **401**.

FIG. **4A** is a schematic view of an avionics software tasking model **500** in accordance with a further embodiment of the invention. In this embodiment, the avionics software tasking model **500** includes a reset capability **502** for initialization of a payload under test. A user **504** may initiate an avionics software task **506** that may use information supplied from a local computing system **508** and from a remote via a communication link (e.g. a Web) **510**. A functional

mode module **512** then receives input from the task **506** and transmits appropriate command signals to a system **514** and to a payload **516**. In turn, the system **514** transmits appropriate commands to one or more components of a driver layer **517**. In this embodiment, the hardware driver layer **517** includes a command and data handling module **518**, a timing module **520**, a fluid systems module **522**, a power distribution and monitoring module **524**, and a ground support system module **526**. A models and simulations module **528** is coupled to the ground support system module **526**, and a payload interface module **530** is coupled to the payload **516**. Finally, a payload test and verification system **550** is coupled to the system module **514**.

In operation, the PTVS **550** is capable of being commanded/monitored via the Web **510** (i.e. Internet) interface or other test routines/simulations found on the system module **514** (e.g. previously loaded from the Internet access or via other portable storage media, including CD-Rom, USB or equivalent Memory Stick, Deployable hard drives, etc.). Software functional modes include a System level (indicating the PTVS) functions and a Payload function. In alternate embodiments, the payload module **516** functionality may be replaced by functionality for any space vehicle or payload while maintaining the overall PTVS capabilities. Only vehicle specific simulations, test scripts, or test parameters must be loaded to assure compatibility.

The system module **514** functionality may provide the System Status (operating parameters of the PTVS **550** and associated equipment), Caution and Warning (associated with Test System maladies and certain warnings/interlocks regarding Payload/Vehicle and Test System interoperability), System Safe Pre-Loads (software configured to position systems in a safe posture in the event of detected malfunction of a critical test capability or vehicle/payload system), and the overall command, control, and monitoring of the payload/vehicle under test as well as the PTVS internal capability. Software capabilities which are subordinate to the system module **514** function include the management of Command and Data Handling, the distribution and management of Timing issues, control and measurements associated with fluid systems under test, the control, distribution and monitoring of Power to the Test System (PTVS) and systems under test, and finally, the command, control and monitoring of ground systems used during the test activity (i.e. pumps, meters, fluid support, data networking, formulation and application of simulations and models with a real-time management capability, data recording and processing, etc.).

FIG. **4B** is a schematic view of the portable test and verification system **550** of FIG. **4A**. In this embodiment, the PTVS **550** includes a processor **552** operatively coupled to a simulations and modeling module **554** and to a data bus **556**. A signal generation module **558** is coupled to the data bus **556** and to a digital switching module **560** which, in turn, is coupled to the payload interface **530** (FIG. **4A**). A signal conditioning module **562** is also coupled between the data bus **556** and the payload interface **530**.

The PTVS **550** further includes a web interface **564** that received inputs from, and transmits outputs to, a remote location. These data are passed through an information sharing protocol server **566**, a modulator/demodulator **568**, and a buffer memory **570** en route to the data bus **556**. Finally, a reflective memory **572** (e.g. a scramnet reflective memory) is coupled to the data bus **556**.

In operation, the PTVS **550** provides a test capability which bridges the gap between the testing of payloads/vehicle institutionally and testing at an advanced spaceport where systems are tested by vehicle and/or payload devel-

opers with the use of spaceport assets relegated to networking systems, common fluid commodities, ground power, data routing, mechanical positioning systems, and the command, control, and monitoring of the mission. With this in mind, the PTVS **550** is capable of supporting command and control via the Internet interface or internal simulations/

models for a payload or vehicle. Command, control, and monitoring of the system under test (payload or vehicle) may be accomplished via the web interface **564** through association with the information sharing protocol server **566** (e.g. using an ISP software load). Upon the demodulation of incoming commands using the modulator/demodulator **568**, the buffer memory **570** acts to preclude command timing issues between the test environment and the external command capability. Application of a command of external origin to the data bus **556** allows the storage of the command in the reflective memory **572** while the same command is examined by the processor **552** and the actions associated with the incoming command are executed. In the event the command requires translation into the payload for an immediate response, the on-board models/simulations contained in the simulations and modeling module **554** are available which correspond to the necessary actions and will trigger the appropriate signal generation from the signal generation module **558**, and gated application using the digital switching module **560**. Analog or digital responses from the payload/vehicle are accommodated by the signal conditioning capability of the signal conditioning module **562** which then routes the digital data to the reflective memory **572** until requested by the processor **552** for use or downloading via the web interface **564**.

It will be appreciated that a primary innovation of the embodiments shown in FIGS. **4A** and **4B** is that the payload and vehicle testing community is enabled to evolve from an institutional testing capability of specialized hardware and software to a capability more akin to a commercial airport operation where vehicle owners provide for the testing and care of mission hardware/software with private resources. Thus, only general support needs to be provided by the launch/landing site(s).

FIG. **5** is an integrated spaceport automated data management architecture **600** in accordance with another alternate embodiment of the invention. In this embodiment, the architecture **600** includes a common infrastructure **602** for the performance of core functions, including, for example, communications and management activities. A plurality of wizard-driven, highly-integrated and distributed modules interface with the common infrastructure **602** to enable inter- and intra-center indications in system operation management. In one particular embodiment, the modules interface to the common infrastructure **602** using computer software (or middleware) that allows the seamless introduction and removal of various functional elements or modules during systems integration, security, and maintenance operations. One example of the middleware that may be used for this purpose is the System/Simulation Infrastructure (S/SI) software developed by The Boeing Company of Chicago, Ill. As described more fully below, the architecture **600** advantageously allows for scalability and system modifiability.

As shown in FIG. **5**, the plurality of modules coupled to the common infrastructure **602** includes a government regulators module **604**, a test range module **606**, and an input module **608**. The input module **608** is operatively coupled to a set of planning modules **610** that includes a scheduling module **612**, a requirement module **614**, a procedure development module **616**, a financial properties module **618** and

a logistics planning modules **620**. Supporting information provided to the planning modules **610** includes weather forecasting information **622** (e.g. winds, sheer warnings, direction, speed, precipitation, lightning, whether system impacts, etc.), safety issues information **624**, traffic control information **626**, and warehousing information **628**.

A test script generation module **630** is also coupled to the common infrastructure **602**. The test script generation module **630** receives requirements satisfaction information **632**, and generates test scripts accordingly. The test scripts may allow automated testing, or testing with human intervention as a priority (e.g. safety, quality checkpoints, etc.), and real-time data reduction. A configuration control module **634** is coupled to the common infrastructure **602** and provides automated acceptance data package management **636**, automated weight balance calculations **638**, and may generate flight certification information (not shown).

An integration simulator module **640** is coupled to the common infrastructure **602** and utilizes maintenance simulation information **642**. The integration simulator module **640** may include, for example, automated cell-verifying interface simulations, maintenance simulations, integration simulations, operation simulations, robotics, and any other suitable simulations. Support for multiple types of spacecraft or payloads are accommodated through the employment of modeled input from the simulation module. Additionally, the combination of Artificial Intelligence **644**, Inspections **646**, and Decision Support module **648** parameters with the Integration Simulation **640** and Maintenance Simulation **642** provide the basis for support of state-of-the-art vehicle and payload testing using non-invasive technologies (i.e. radio frequency resonance, quantum resonance, magnetic resonance, etc.).

An artificial intelligence module **644** is also coupled to the common infrastructure **602**, and utilizes inspection information **646**, decision-support information **648**, and environmental support information **650**. The artificial intelligence module **644** may perform artificial vision functions (e.g. for inspections and validations), decision-support functions, and other suitable functions.

The common infrastructure **602** is coupled by a communications link **660** to one or more distributed teams, centers, payload processing facilities, vehicle processing facilities, or other interested parties involved in the payload integration process. This link allows for the on-runway or launch pad location access of the vehicle or payload to diagnostic information from the equipment operator. This is provided from transmission points embedded strategically near and at the points of convergence of the vehicle to the launch point. These access points accommodate the vehicle or payload owners access to equipment without Spaceport mediation.

Embodiments of integrated spaceport automated data management architecture **600** in accordance with the present invention may provide significant advantages over the prior art. For example, architectures in accordance with the present invention may render fully-integrated functionality to support the implementation of advanced spaceport launch facilities, without presupposing any specific launch vehicle or type of vehicle (vertical or horizontal operations). The architecture **600** encompasses all major data resources required to support the ground operations of an operational spaceport for commercial or governmental use. Furthermore, architectures in accordance with the present invention suppose any spaceport as a no-load on a national (or global depending upon the implementation) domain. Therefore, the capacity to plug the spaceport into the major network or

11

withdraw as operational conditions arise in the seamless manner is also supposed in the architecture.

A payload lifecycle **700** in accordance with yet another embodiment of the invention will now be described. In this embodiment, the lifecycle **700** includes preflight operations **702**. The preflight operations **702** may include those preflight operations associated with the preparation of a payload **704** as well as those associated with a launch vehicle **706**. More specifically, the preflight operations **702** may include the performance of payload test and verification activities using one or more embodiments of apparatus and methods in accordance with the present invention, including those embodiments described above with reference to FIGS. 1-5.

In a presently preferred embodiment, the lifecycle **700** also includes flight system integration activities **708**, including the integration of the payload within the launch vehicle. Servicing and departure activities **710** are also performed. A desired mission **712** (e.g. a spaceflight) is then performed using the payload and the launch vehicle. The lifecycle **700** also includes landing and recovery activities **714** and turnaround preparations **716**. Following the turnaround preparations **716**, alternatives include providing deliverables to a payload customer **718** (e.g. test data, information, hardware, specimens, etc.), returning the launch vehicle to preflight operations **720**, and returning the payload to preflight operations **722**.

It will be appreciated that embodiments of methods and systems for information management in accordance with the present invention are applicable to a spaceport application supporting multiple types of spacecraft and payload configurations. Embodiments of the present invention are capable of enabling the testing of payload elements in an autonomous fashion under direct and indirect control of the payload developer. Thus, the testing of individual payloads may be transitioned to the payload developer and undertaken during space delivery system pre-flight operations through an autonomous communications link under the payload developer's control. Consequently, mission operations may be provided by the payload developer autonomously via the communications link, software, or artificially derived knowledge. As used herein, the term artificially derived knowledge includes knowledge which is attained as a result of the implementation of rules, interpolation of naturally or artificially occurring data, or derived from sensory input manipulation (e.g. knowledge output from an artificial intelligence engine or experiences of a sensory device).

Embodiments of payload lifecycles in accordance with the present invention may provide significant advantages over the prior art. For example, because the preflight operations involving the payload **704** may utilize apparatus and methods of test and verification of the payload in accordance with the present invention, the overall payload lifecycle may be improved. More specifically, embodiments of the present invention provide Web-accessible data retrieval systems that utilizes semantic data relationship to render search and retrieval of multisensor data residing on a single or multiple databases.

Embodiments of the present invention may also enable the use of a common set of processes and tools for increased cost savings through significantly increased synergy across payload life cycle activities (such as development, test and certification, on orbit operations, and post-mission data reduction and analysis) and organizations. This is accomplished through the implementation of a reusable payload checkout system framework with a flexible and well-integrated suite of services. The framework will permit the services to be deployed in remotely distributed geographic

12

locations for use by payloads stakeholders alone, in local communities, or together as collaborative teams.

Payload lifecycle activities are currently performed by a number of loosely integrated and, at times, disjoint "fiefdoms". Many organization-unique processes and tools are used to support similar capabilities and the very same program data products, like the command and measurement tables, are often reengineered by each organization for compatibility with their system. Embodiments of apparatus and methods in accordance with the present invention, however, will permit the entire payloads community to standardize and use tailor-able, mature processes that embody the current best practices of payload processing.

While preferred and alternate embodiments of the invention have been illustrated and described, as noted above, many changes can be made without departing from the spirit and scope of the invention. Accordingly, the scope of the invention is not limited by the disclosure of the preferred and alternate embodiments. Instead, the invention should be determined entirely by reference to the claims that follow.

What is claimed is:

1. A payload life cycle apparatus, comprising:

a preflight operations portion that includes a payload test procedure, the payload test procedure including:

transmitting one or more test signals that emulate an anticipated condition from a test system to the payload;

receiving one or more responsive signals from the payload into the test system;

analyzing one or more responsive signals; and

determining whether one or more of the responsive signals comprises an anomalous signal,

wherein at least one of the transmitting, receiving, analyzing, and determining comprises communicating via a communications link from a payload processing facility to a remotely located facility;

a flight system integration portion that includes integration of the payload within a launch vehicle; and a desired mission portion.

2. The payload life cycle of claim 1, wherein the payload test procedure is further adapted to communicate via an Internet link from a payload processing facility to a remotely located facility.

3. The payload life cycle of claim 1, wherein the payload test procedure is further adapted to communicate via a communications link from a payload processing facility to a launch facility.

4. The payload life cycle of claim 1, wherein the payload test procedure is further adapted to communicate via a communications link from at least one of a first city to a second city, a first state to a second state, and a first country to a second country.

5. The payload life cycle of claim 1, wherein the payload test procedure is further adapted to at least one of identify an occurrence of an anomalous condition to a system operator via a display, query a system operator whether to generate a nonconformance report, transmit a nonconformance report to a remotely located data storage facility, query a system operator whether to retest a nonconforming condition, and troubleshoot a nonconforming condition via the communication link between the payload processing facility to the remotely located facility.

6. The payload life cycle of claim 1, wherein the preflight operations portion further includes a preparation procedure associated with a launch vehicle.

7. The payload life cycle of claim 1, further comprising a servicing and departure portion.

13

8. The payload life cycle of claim 1, further comprising at least one of a landing and recovery portion, a turnaround preparations portion, and a providing deliverables to a payload customer portion.

9. The payload life cycle of claim 1, wherein the preflight operations portion includes a spaceport application having a plurality of preflight subportions, each preflight subportion supporting at least one of a plurality of spacecraft configurations and a plurality of payload configurations.

10. The payload life cycle of claim 1, wherein the payload test procedure includes testing of at least one payload element autonomously by a payload developer at the remotely located facility via the communications link.

14

11. The payload life cycle of claim 1, wherein the payload test procedure includes transitioning of an individual payload test procedure to a payload developer at the remotely located facility via an autonomous communications link controlled by the payload developer.

12. The payload life cycle of claim 1, wherein the desired mission portion includes autonomously providing at least one mission operation from the payload integrated with the launch vehicle by the payload developer via at least one of a mission communications link, a software portion, and an artificially derived knowledge.

* * * * *